

H. 最大移動速度和最大長度

KM系列受到滾珠螺桿的危險轉速和DN值的限制，其各規格之最大移動速度如下所示。

單位：mm

型號	螺桿導程	軌道長度	最大移動速度(mm/s)			最大長度				
			普通級 N	高級 H	精密級 P	普通級 N	高級 H	精密級 P		
KM 26	2	150	280	280	280	300	300	300		
		200								
		250								
	6	300	590	590	830	300	300	300		
		150								
		200								
KM 30	5	250	390	390	550	600	600	600		
		300								
		400								
		500								
		600								
		340								
	10	150	790	790	1100	600	600	600		
		200								
		300								
		400								
		500			980					
		600			650				650	650
KM 33	5	150	390	390	550	600	600	600		
		200								
		300								
		400								
		500								
		600							340	340
	10	150	790	790	1100	600	600	600		
		200								
		300								
		400								
		500			980					
		600			650				650	650
KM 45	10	340	520	520	740	940	940	740		
		440								
		540								
		640								
		740			730					
		940			430				430	-
	20	340	1050	1050	1480	940	940	740		
		440								
		540								
		640								
		740			1440					
		940			840				840	-
KM 46	10	340	520	520	740	940	940	740		
		440								
		540								
		640								
		740			730					
		940			430				430	-
	20	340	1050	1050	1480	940	940	740		
		440								
		540								
		640								
		740			1440					
		940			840				840	-
KM 55	20	980	800	800	1120	1380	1380	1180		
		1080								
		1180								
		1280			900					
		620			740				740	-
		1380			530				530	-